



**PX2KREX**

Ex e Ex d Ex nR Ex ta

**PX2KREX Globally Approved, Explosive Atmosphere RapidEx Barrier Cable Gland**

**For all types of Armoured Cables**

- RapidEx liquid pour sealing system
  - Enhances reliability, reduces risk
  - Reduces man hours
  - Reduces cost
- Metal-to-metal armour clamping
- Direct & remote installation
- Integral protected deluge seal
- Controlled outer 'load retention' seal
- Unique OSTG prevents overtightening
- -60°C to +85°C
- Globally marked, IECEx, ATEX & cCSAus
- Superior EMC performance



† Grooved Cone (X) is predominantly used for Wire Braid (e.g. GSWB, TCWB), Steel Tape Armour (STA, DSTA) and Aluminium Strip Armour (ASA) but is also suitable for Single Wire Armour (SWA), Aluminium Wire Armour (AWA) and Pliable Wire Armour (PWA) if the range is outside that of the Stepped Cone (W).

Grooved Cone (X) dimensions shown in the Cable Gland Selection Table below are for a double wire strand of braid armour cables. Tapes can also be doubled over. For cables that have only a single layer of armour such as SWA the clamping range should be used as shown in the table below.

Stepped (W) Cone is suitable for Single Wire Armour (SWA), or Aluminium Wire Armour (AWA) cables.

**TECHNICAL DATA**

<b>Design Specification</b>	BS 6121:Part 1:1989, IEC 62444, EN 62444
<b>Mechanical Classifications*</b>	Impact = Level 8, Cable Anchorage = Class D
<b>Enclosure Protection</b>	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
<b>Electrical Classifications*</b>	Category B (Category A when used with braid, tape or pliable wire armour cables)
<b>ATEX Certificate</b>	SIRA13ATEX1072X, SIRA13ATEX4078X
<b>Code of Protection</b>	Ⓢ II 2G, II 1D, Ex d IIC Gb, Ex e IIC Gb, Ex ta IIIC Da Ⓢ II 3G Ex nR IIC Gc, Ⓢ IM2 Ex d I Mb, Ex e I Mb
<b>Compliance Standards</b>	EN 60079-0,1,7,15,31
<b>IECEx Certificate</b>	IECEx SIR 13.0027X, IECEx SIM 14.0008X
<b>Code of Protection</b>	Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex d I Mb, Ex e I Mb
<b>Compliance Standards</b>	IEC 60079-0,1,7,15,31
<b>cCSAus Certificate (20S16 - 100)</b>	2288626
<b>CSAus Code of Protection***</b>	Class I, Div. 1, 2 Groups A, B, C and D; Class II, Div. 1, 2 Groups E, F and G; Class III, Div. 1, 2; Type 4X: Oil Resistant II: Class I, Zone 1 AEx d IIC Gb, AEx e IIC Gb, Class I, Zone 2 AEx nR IIC Gc, Class I, Zone 20 AEx ta IIIC Da
<b>cCSA Code of Protection***</b>	Class I, Div. 1, 2 Groups A, B, C and D; Class II, Div. 1, 2 Groups E, F and G; Class III, Div. 1, 2; Type 4X: Oil Resistant II: Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da
<b>Compliance Standards</b>	CAN/CSA-C22.2 No 0,18,25,30,94,174, CAN/CSA-E60079-0,1,7,15,31 CAN/CSA-E612411 Part 11, ANSI/UL 514B Ed 5, ANSI/UL 50 Ed 11, ANSI/UL 2225 Ed 4, UL60079
<b>EAC Certificate</b>	TC RU C-GB.AA87.B.00487
<b>UkrSEPRO</b>	UA.TR.047.C.0644-15
<b>CCOE / PESO (India) Certificate</b>	P333688
<b>NEPSI Certificate</b>	GYJ18.1252X
<b>INMETRO Approval</b>	TÜV 12.2073X
<b>RETIE Approval Number</b>	03866
<b>Marine Approvals</b>	LRS: 01/00172 DNV: TAE000000Y ABS: 14-LD234401A-4-PDA, BV: 43180 A1 BV
<b>Ingress Protection Rating**</b>	IP66, IP67 & IP68****
<b>Deluge Protection Compliance</b>	DTS01 : 91
<b>Cable Gland Material</b>	Brass, Electroless Nickel Plated Brass, Stainless Steel, Aluminium
<b>Seal Material</b>	CMP SOLO LSF Halogen Free Thermoset Elastomer / RapidEx Resin Barrier
<b>Cable Type</b>	Single Wire Armour (SWA), Aluminium Wire Armour (AWA), Wire Braid Armour (e.g. SWB), Screened Flexible (EMC) Wire Braid (e.g. CY / SY), Pliable Wire Armour (PWA), Steel Tape Armour (STA), Strip Armour (e.g. ASA)***
<b>Armour Clamping</b>	Detachable Resin Tube / Cone or AnyWay Universal Clamping Ring
<b>Sealing Technique</b>	Unique CMP 'LRS' Outer Seal (Load Retention Seal)
<b>Sealing Area(s)</b>	Inner RapidEx Barrier Seal & Outer Sheath

\* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444

\*\* When CMP installation accessories are used. Refer to page 7 or www.cmp-products.com for further information.

\*\*\*Where the cable is permitted by code (NEC and/or CEC)

\*\*\*\* IP68 tested to a minimum depth of 30 metres for 12 hours, alternate depths / durations can be provided upon request

**Cable Gland Selection Table**

Refer to illustration at the top of the page.

Dimensions listed below are for metric cable glands only  
Dimensions for alternative threads may vary, please see supplementary technical data sheet

Cable Gland Size	Available Entry Threads "C" (Alternate Metric Thread Lengths Available)				Number of Cores	Diameter Over Conductors "A"	Cable Bedding Diameter "C"	Overall Cable Diameter "B"				Armour Range †				Across Flats "D"	Across Corners "D"	Protrusion Length "F"	Combined Ordering Reference (*Brass Metric)			Shroud	Cable Gland Weight (Kgs)
	Standard		Option					Min	Max	Min	Max	Min	Max	Min	Max				Size	Type	Ordering Suffix		
	Metric	Thread Length (Metric) "E"	NPT	Thread Length (NPT) "E"																			
20S16	M20	15.0	1/2"	19.9	3/4"	11	11.7	11.7	6.1	13.1	0.3	1.0	0.8	1.25	30.5	33.6	62.0	20S16	PX2KREX	1RA	PVC06	0.24	
20S	M20	15.0	1/2"	19.9	3/4"	11	11.7	11.7	9.5	15.9	0.3	1.0	0.8	1.25	30.5	33.6	62.0	20S	PX2KREX	1RA	PVC06	0.23	
20	M20	15.0	1/2"	19.9	3/4"	11	12.6	12.9	12.5	20.9	0.4	1.0	0.8	1.25	30.5	33.6	63.0	20	PX2KREX	1RA	PVC06	0.24	
25S	M25	15.0	3/4"	20.2	1"	21	17.5	17.9	14.0	22.0	0.4	1.2	1.25	1.6	37.5	41.3	69.5	25S	PX2KREX	1RA	PVC09	0.37	
25	M25	15.0	3/4"	20.2	1"	21	17.5	17.9	18.2	26.2	0.4	1.2	1.25	1.6	37.5	41.3	69.5	25	PX2KREX	1RA	PVC09	0.37	
32	M32	15.0	1"	25.0	1 1/4"	38	23.6	23.9	23.7	33.9	0.4	1.2	1.6	2.0	46.0	50.6	75.0	32	PX2KREX	1RA	PVC11	0.57	
40	M40	15.0	1 1/4"	25.6	1 1/2"	59	30.0	30.3	27.9	40.4	0.4	1.6	1.6	2.0	55.0	60.5	75.0	40	PX2KREX	1RA	PVC15	0.80	
50S	M50	15.0	1 1/2"	26.1	2"	89	36.6	36.9	35.2	46.7	0.4	1.6	2.0	2.5	60.0	66.0	77.0	50S	PX2KREX	1RA	PVC18	0.90	
50	M50	15.0	2"	26.9	2 1/2"	89	41.0	41.3	40.4	53.0	0.6	1.6	2.0	2.5	70.0	77.0	77.0	50	PX2KREX	1RA	PVC21	1.19	
63S	M63	15.0	2 1/2"	26.9	2 1/2"	115	47.9	48.4	45.6	59.4	0.6	1.6	2.0	2.5	75.0	82.5	79.7	63S	PX2KREX	1RA	PVC23	1.39	
63	M63	15.0	2 1/2"	39.9	3"	115	53.7	54.0	54.6	65.8	0.6	1.6	2.0	2.5	80.0	88.0	80.3	63	PX2KREX	1RA	PVC25	1.41	
75S	M75	15.0	2 1/2"	39.9	3"	140	59.9	60.2	59.0	72.0	0.6	1.6	2.0	2.5	90.0	99.0	86.8	75S	PX2KREX	1RA	PVC28	2.09	
75	M75	15.0	3"	41.5	3 1/2"	140	64.2	64.2	66.7	78.4	0.6	1.6	2.5	3.0	100.0	110.0	88.3	75	PX2KREX	1RA	PVC30	2.54	
90	M90	24.0	3 1/2"	42.8	4"	200	75.3	75.6	76.2	90.3	0.8	1.6	3.15	4.0	115.0	126.5	102.1	90	PX2KREX	1RA	PVC32	3.71	
100	M100	24.0	3 1/2"	42.8	4"	200	85.6	85.9	86.1	101.4	0.8	1.6	3.15	4.0	127.0	139.7	114.0	100	PX2KREX	1RA	LSF33	4.27	

\* For material options add the following suffix to the Ordering Reference; Brass (no suffix required); Nickel Plated Brass 'S'; 316 Grade Stainless Steel '4'; Copper Free Aluminium '1'  
For NPT options please add the following digits to the material suffix; 1/8" = 31, 3/4" = 32, 1" = 33, 1 1/4" = 34, 1 1/2" = 35, 2" = 36, 2 1/2" = 37, 3" = 38, 3 1/2" = 39, 4" = 40 (Brass requires prefix "0")

Examples: 32PX2KREX1RA534 = Nickel Plated Brass 1 1/4" NPT, 50SPX2KREX1RA035 = Brass 1 1/2" NPT, 25PX2KREX1RA432 = Stainless Steel 3/4" NPT, 20PX2KREX1RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated