



- The latest LED technology with a high luminous efficacy and a long service life
- Extremely high luminaire efficacy
- Variants with 90 minutes or 180 minutes emergency lighting duration available
- Luminous flux after 100,000 h still 90% of the starting luminous flux
- Optionally with DALI for controlling and monitoring the luminaire
- Automatic weekly function test and annual rated operating time test

E2

MY R. STAHL 6409C



The emergency luminaire with Series 6409/4 LED with integrated battery can be installed in stand-by switching, continuous mode or in switchable stand-by switching. A weekly functional test and annual rated operating time test are performed automatically. The results are indicated by an LED.

	IECEx / ATEX					
Zone	0	1	2	20	21	22
Installation in		•		•	•	

Selection Table									
Size 2 Lamp wattage 25 W Luminaire efficacy 116 lm/W Luminous flux 2910 lm									
Light colour Operating time Ballast Disconnection of the luminaire Threaded plate Drilled holes Through wiring Product Type Art. No. Weight									
5000 K – neutral white 1.5h emergency lighting operation LED NLE 80W 110-240V/7Ah/1.5h/ Only battery 2x plastic 3 x M25 With 6 conductors 2.5 mm ² 6409/4128-5101-162-1110-11-850011 271816 5.4 kg									
LED NLE 80W 110-240V/7Ah/1.5h/ All-pole disconnection 2x plastic 3 x M25 With 6 conductors 2.5 mm ² 6409/4128-5103-162-1110-11-850011 267859 5.4 kg									
LED NLE 80W 110-240V/7Ah/1.5h/ All-pole disconnection 2x SS430 stainless steel 3 x M20 With 6 conductors 2.5 mm ² 6409/4128-5103-162-2220-22-850011 271825 4.7 kg									
LED NLE 80W 110-240V/7Ah/1.5h/ All-pole disconnection 2x plastic 3 x M25 With 8 conductors 2.5 mm ² 6409/4128-5113-182-1110-11-850011 276234 5.4 kg									
3h emergency lighting operation LED NLE 80W 110-240V/7Ah/3.0h/ All-pole disconnection 2x plastic 3 x M25 With 6 conductors 2.5 mm ² 6409/4128-5203-162-1110-11-850011 267860 5.4 kg									
LED NLE 80W 110-240V/7Ah/3.0h/ All-pole disconnection 2x SS430 stainless steel 3 x M20 With 6 conductors 2.5 mm ² 6409/4128-5203-162-2220-22-850011 272458 5.4 kg									
Size 4 Lamp wattage 45 W Luminaire efficacy 129 lm/W Luminous flux 5810 lm									
Light colour Operating time Ballast Disconnection of the luminaire Threaded plate Drilled holes Through wiring Product Type Art. No. Weight									
4000 K – warm neutral white 3h emergency lighting operation LED NLE 80W 110-240V/7Ah/3.0h/ All-pole disconnection 2x plastic 3 x M25 With 6 conductors 2.5 mm ² 6409/4148-5203-162-1110-11-840011 277319 8.1 kg									

Selection Table

Size	4	Light colour	Operating time	Ballast	Disconnection of the luminaire	Threaded plate	Drilled holes	Through wiring	Product Type	Art. No.	Weight
Lamp wattage	45 W	5000 K – neutral white	1.5h emergency lighting operation	LED NLE 80W 110-240V/7Ah/ 1.5h/	Only battery	2x plastic	3 x M25	With 6 conductors 2.5 mm ²	6409/4148-5101-162-1110-11-850011	271004	8.1 kg
Luminaire efficacy	129 lm/W			LED NLE 80W 110-240V/7Ah/ 1.5h/	All-pole disconnection	2x plastic	3 x M25	With 6 conductors 2.5 mm ²	6409/4148-5103-162-1110-11-850011	267861	8.1 kg
Luminous flux	5810 lm			LED NLE 80W 110-240V/7Ah/ 1.5h/	All-pole disconnection	2x SS430 stainless steel	3 x M20	With 6 conductors 2.5 mm ²	6409/4148-5103-162-2220-22-850011	271585	8.1 kg
		3h emergency lighting operation	LED NLE 80W 110-240V/7Ah/ 3.0h/	All-pole disconnection	2x plastic	3 x M25	With 6 conductors 2.5 mm ²	6409/4148-5203-162-1110-11-850011	267862	8.1 kg	
			LED NLE 80W 110-240V/7Ah/ 3.0h/	All-pole disconnection	2x SS430 stainless steel	3 x M20	With 6 conductors 2.5 mm ²	6409/4148-5203-162-2220-22-850011	272470	8.1 kg	

Variants with 2 x threaded plate plastic and 3 x drilled holes M25:

Cable glands 2 x M25 Ø 7-17 mm and 2 x stopping plugs M 25 x 1,5 are included loose with the product (installation required). Threaded plate included.

Variants with 2 x threaded plate stainless steel SS430 and 3 x drilled holes M20:






Cable glands and stopping plugs can be ordered as accessories. Threaded plate included.





The light fittings are supplied without mounting material.



Technical Data

Variant	Size 2	Size 4
Explosion Protection		
IECEx gas explosion protection	Ex db ec IIC T4 Gc	Ex db ec IIC T4 Gc
IECEx dust explosion protection	Ex tb op is / tc IIIC T100 °C Db	Ex tb op is / tc IIIC T100 °C Db
IECEx dust explosion protection 2	Ex tc IIIC Db	Ex tc IIIC Db
ATEX gas explosion protection	II 3 G Ex db ec IIC T4 Gc	II 3 G Ex db ec IIC T4 Gc
ATEX dust explosion protection	II 2 D Ex tb op is / tc IIIC T100 °C Db	II 2 D Ex tb op is / tc IIIC T100 °C Db
ATEX dust explosion protection 2	II 2 D Ex tc IIIC Db	II 2 D Ex tc IIIC Db
Note: Through wiring	Max. 3x16 A	Max. 3x16 A
Note: Through wiring 2	Max. 3x10 A	Max. 3x10 A
Certificates	ATEX (IBE), IECEx (IBE), India (PESO)	ATEX (IBE), IECEx (IBE), India (PESO)
Declaration of conformity	ATEX (EUK), Declaration of Conformity (AUS)	ATEX (EUK), Declaration of Conformity (AUS)
Electrical Data		
Rated operational voltage AC	110 ... 240 V	110 ... 240 V
Battery operating voltage	6 V	6 V
Battery capacity	7 Ah	7 Ah
Frequency range	50 – 60 Hz	50 – 60 Hz
Battery version	NiCd battery, gas-tight	NiCd battery, gas-tight
Ambient Conditions		
Ambient temperature °C	-30 – 50 °C	-30 – 50 °C
Ambient temperature	-30 °C ... +50 °C Note: Through wiring Max. 3x16 A -30 °C ... +55 °C Note: Through wiring 2 Max. 3x10 A	-30 °C ... +50 °C Note: Through wiring Max. 3x16 A -30 °C ... +55 °C Note: Through wiring 2 Max. 3x10 A
Lighting Data		
Number of lamps	1	1
Lamp	LED	LED
Light distribution	120°x120° with diffusing glass	120°x120° with diffusing glass
Colour rendering	≥ 80	≥ 80
Colour temperature	5000 K	4000 K

Technical Data		
Variant	Size 2	Size 4
Mechanical Data		
Enclosure material	Polyester resin, Glass fibre reinforced	Polyester resin, Glass fibre reinforced
Diffuser	With diffuser	With diffuser
Sealing material	Silicone	Silicone
Installed terminal strip	PE + N + L1 + L2 + L3 + L'	PE + N + L1 + L2 + L3 + L'
Max. solid connection terminals	6 mm ²	6 mm ²
Max. finely stranded connection terminals	4 mm ²	4 mm ²
Type of connection cable	Finely stranded Solid	Finely stranded Solid
Impact strength (IEC 62262)	IK10	IK10
Enclosure colour	Light grey (RAL 7035)	Light grey (RAL 7035)
Notes	Connection terminals: Spring clamp terminal (2 free clamping units per pole)	
Components		
Cable glands and entries	2 x M25 Ø 7 ... 17 mm	2 x M25 Ø 7 ... 17 mm
Cable entry material	Polyamide, black	Polyamide, black
Stopping plugs	2 x M25 x 1.5	2 x M25 x 1.5
Stopping plug material	Polyamide, black	Polyamide, black


Accessories			
Figure	Description	Art. No.	Weight
	Thread: M25 x 1.5 (20 pieces); without jam nut	285780	200 g
	M25 x 1.5 in order to avoid condensate formation	115738	17 g
	Thread: M25 x 1.5 (1 piece); for installation in light fittings; made from stainless steel; without jam nut	296608	76 g
	The fall prevention system for the light fitting cover prevents the light fitting cover from falling accidentally when the light fitting is opened.	226791	21 g
	for the subsequent mounting on lights size 2 and size 4, completely with assembly parts (for pipe diameter 42 mm)	227512	3.2 kg
	The protection against accidental contact prevents maintenance technicians and electrical installers from accidentally touching conductive parts. The degree of protection is increased to IP20 when the protection against accidental contact is used.	283153	14 g
	M8 / A/F 13; For actuating the central lock	222430	110 g

Accessories			
Figure	Description	Art. No.	Weight
Mounting rail	 for a variable mounting distance; 1 pair	222826	350 g
Mounting bracket	 mounting clamp mounted on a mounting rail for a variable mounting distance; 1 pair	222456	400 g
Pipe clamp	 R 1 1/2"; with mounting rail for a variable mounting distance; material: stainless steel; 1 pair R 1 1/4"; with mounting rail for a variable mounting distance; Material: stainless steel; 1 pair R 2"; with mounting rail for a variable mounting distance; Material: stainless steel; 1 pair	222459 222458 222460	700 g 700 g 750 g
Ring bolt	 M8, direct mounting in insert nuts; 1 pair	115736	115 g
Ceiling and wall mounting bracket	 mounted on a mounting rail for a variable mounting distance; Material: stainless steel; Lamp can be swiveled in steps of 15°; 1 pair	222827	1.2 kg


Spare Parts			
Figure	Description	Art. No.	Weight
Cover	 for luminaire size 4 for luminaire size 2	222428 222427	1.15 kg 639 g
Contact element	 8080/1-3-L 2 NC contact element	132527	26 g
Battery set	 Battery cover with built-in battery. Gas-tight NiCd battery; 7 Ah / 6 V	223532	1.2 kg

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations


E2




E2




A



Wall mounting bracket fitted in mounting rail



Size 2



Size 4